



KUZMA STABI R WOOD FRAME ASSEMBLY- in the photo, a wooden frame fitted with Stabi R base turntable

Instruction manual

2022-07

KUZMA LTD

INSTRUCTION MANUAL FOR STABI R WOODEN FRAME ASSEMBLY-PLINTH

The **Stabi R** base turntable can be fitted into the Kuzma supplied wooden frame -plinth.

CONTENTS:	Page
General	2
Technical data	2
Unpacking	2
Preparing Stabi R	3
Assembling	3
Tonearm mounting	4
Maintenance	4

General

Stabi R wooden frame-plinth is made from solid walnut and plywood into which you can fit the Stabi R base turntable. The armboard block is supplied with the Kuzma 9 inch arm cut.

The Stabi R plinth is supported on three fully adjustable metal feet.

For more details read instruction manual for Stabi R wood turntable and check plinth dimensions which are both available on our web site.

Technical data:

Mass	9 kg
Plinth:	walnut(oil protected)
Levelling	yes (3 adjustable feet)
Armboard	yes (armboard block)
No. of tonearms	1
Dimensions	500 x 463 x 113 mm
Accessories supplied	Torx bit T30, screws 3 x M6x40, 2x wooden screws

Basic Setup

Note: Some parts are heavy, so be careful when handling!

Note: Choose a suitable supporting table which can hold over 40 kg without warping.

Unpacking

The plinth is packed in one box. Before unpacking prepare the area where the assembly will take place. The best position is on a solid table which is strong and rigid enough to support 40-50 kg.

Preparing Stabi R for plinth fitting

Depending on which version of the turntable you have, remove all parts from the base: platter, belt, subplatter, tonearm, armwing, arm holders, arm balconies, supporting spikes, side panels, unplug cable and it is best to remove the bearing shaft with oil reservoir by removing 3 screws using Allen key 3 mm. See Fig. 1.&2.



Fig. 1. Stabi R base top view



Fig. 2. Stabi R base bottom view

Assembling

Place the sheet of white foam from packing box on the table.

Place Stabi R base with the top down. See Fig. 2.

Over Stabi R base put plinth face down over the base. See Fig. 3.

Check alignment of holes and manually fit three fixing screws M 6x40 and secure them by using Allen key 5mm. See Fig. 3.

Turn the whole assembly turn back and remove foam. Be careful-it is heavy. See Fig. 4.

Position turntable over the edge of table to fix armboard block. Fix 2 wooden screws into armboard block. See Fig. 5.

Then return bearing shaft with reservoir and assemble turntable.



Fig. 3. Plinth-bottom view



Fig. 4. Stabi R base fitted into plinth

Tonearm mounting

Mount the arm as instructed in the tonearm instruction manual. The armboard block is fixed in the plinth. Under the arm cutout is hole with access underneath to fix the armbase. If required route the tonearm cable underneath.



Fig. 5. Stabi R with plinth

Maintenance

Wood:

Wipe with damp cloth or special tissues for oiled wood.

Kuzma Ltd

Hotemaze 17A

SI-4205 PREDDVOR

SLOVENIJA

Phone: + 386 4 25 35 450

Fax: + 386 4 25 35 454

E mail: kuzmaltd@siol.net.

www.kuzma.si